

# Aquaseal

The  
All-Weather  
Isolator



# Aquaseal Isolators

Clipsal's Aquaseal is a breakthrough in weatherproof isolator technology. It's the first product of its kind to feature an integral co-moulded sealing system that ensures IP66 protection is maintained and there are no gaskets to get lost or damaged. Match this with Clipsal's innovations in isolator switch design and you have the ideal product for every isolator application.

Aquaseal's modern design is neat and compact and the large actuator switch is easy to use with gloved hands. It also has a locking off facility.

Aquaseal CSS Series Isolators come in 20A, 32A and 40A ratings and are available in single, double, triple pole and four pole versions. Two 25mm threaded entries at the top and 2x20mm at the bottom enable easy conduit access. There are also 25mm cut-out guides at the back of the unit. Large 8mm diameter terminals and fixed looping terminals also make Aquaseal easy to install.

## Aquaseal Features

- Dimensions 162H x 82W x 74D
- Captive Combination Head Screws for your choice of Screwdriver.
- Self threading screws will not work into backbox during transit.
- Large 10mm<sup>2</sup> Cable Conductor Terminals.
- Steel plated terminal screws will never break.
- Co-moulded sealing system so no gaskets will get lost or damaged.
- Large padlocking capacity – suit industry 6mm padlock.
- Backbox comes complete with 2x20mm and 2x25mm. Simply rotate the backbox to suit application.
- Premium moulding materials, chemically resistant and UV stabilised (see your Clipsal representative for a detailed table).
- Also available in Neon version.
- Made in Australia AS/NZS60947-3.



Cover Mounted Switch

## Base Mounted Switch

Cat. No.	Description	M Rating	AC21A	AC22A	AC23A
CSS420	Isolator 4P 20A 415V	M100	20	20	20
CSS432	Isolator 4P 32A 415V	M100	32	32	20
CSS440	Isolator 4P 40A 415V	M100	40	40	20

Cat. No.	Description	M Rating
CSS120	Isolator 1P 20A 250V	M120
CSS132	Isolator 1P 32A 250V	M120
CSS140	Isolator 1P 40A 250V	M120
CSS220	Isolator 2P 20A 500V	M100
CSS232	Isolator 2P 32A 500V	M100
CSS240	Isolator 2P 40A 500V	M100
CSS320	Isolator 3P 20A 500V	M100
CSS332	Isolator 3P 32A 500V	M100
CSS340	Isolator 3P 40A 500V	M100

Products of Clipsal Australia Pty Ltd  
ABN 27 007 873 529

Head Office  
12 Park Terrace, Bowden  
South Australia 5007  
Telephone (08) 8269 0511  
Facsimile (08) 8340 1724  
Internet clipsal.com  
E-Mail plugin@clipsal.com.au

Offices in all States

NSW Sydney	(02) 9794 9200
Albury	(02) 6041 2377
VIC Melbourne	(03) 9207 3200
Country Areas	1800 653 893
QLD Brisbane	(07) 3244 7444
Townsville	(07) 4729 3333

SA Adelaide	(08) 8268 0400
WA Perth	(08) 9442 4444
TAS Launceston	(03) 6343 5900
NT Darwin	(08) 8947 0278

International Enquiries  
International Sales and Marketing  
Telephone + 61 8 8269 0587  
Facsimile + 61 8 8340 7350  
E-Mail export@clipsal.com.au

New Zealand  
Clipsal Industries (NZ) Ltd  
Telephone (09) 576 3403  
Facsimile (09) 576 1015  
E-Mail headoffice@clipsal.co.nz

Customer Service  
Free Fax (0508) 250 305  
Auckland/Mobile Phone (09) 572 0014  
Free Phone (0508) CLIPSAL  
2 5 4 7 7 2 5

You can find this brochure and many others online in PDF format at: clipsal.com  
Follow the links off the home page or access the following page directly:  
clipsal.com/wat\_lib\_pdf.cfm

**clipsal.com**

Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.