# Clipsal Iconic™ Electronic Mechanisms – Selection chart











| | Timers | Dimmers | | | | USB chargers | | | Sensor |
|---|---|---|---|---|---|---|---|---|---|
| **Product Name** | **Timer 10A** | **Rotary LED Dimmer 2-Wire** | **Rotary Push dimmer 2-Wire** | **Push Button Dimmer 2-Wire** | **Rotary 1-10VDC Dimmer** | **Dual Port 45W USB Charger** | **Dual Port 65W USB Charger** | **Dual Port 3.1A USB A+C Charger** | **PIR Motion Sensor Mech** |
| Model # | 40E10PBTM-VW | 40ERDM-VW | 40ERPBDM-VW | 40EPBDM-VW | 40ER110DM-VW | 40E2USBC45M-VW | 40E2USBC65M-VW | 40E2USBACM-VW | 41EPIRM-TN |
| 2-wire / 3-wire | 3-wire | 2-wire (separately switched) | 2-wire (integrally switched) | 2-wire (integrally switched) | 2-wire | Active, neutral | Active, neutral | Active, Neutral | 3-wire |
| Multiway control | Yes (via ControlLink) | Suitable for 1/2 way switching | Multi-way parallel dimming (4-way) | Multi-way parallel dimming (4-way) | NA | NA | NA | NA | Can parallel multiple devices |
| Configurable LED indicator | LED present but not configurable | NO | YES (white or blue) | YES (white or blue) | NA | NA | NA | NA | LED present but not configurable |
| Configurable min/max brightness | NA | YES (min) | YES (min and max) | YES (min and max) | YES (Min) | NA | NA | NA | NA |
| Min load | NA | 3W | 3W | 3W | NA | NA | NA | NA | NA |
| Max load | 10AX/15A Res | 350W | 350W | 350W | 50mA Sink (Passive device) | 2x Type C<br>5 V = 3 A (15W)<br>9 V = 3 A (27W)<br>12 V = 3 A (36W)<br>15 V = 3 A (45W)<br>20 V = 2.25 A (45W) | 2x Type C<br>5 V = 3 A (15W)<br>9 V = 3 A (27W)<br>12 V = 3 A (36W)<br>15 V = 3 A (45W)<br>20 V = 3.25 A (65W) | 2.4 A (Type A),<br>3 A (Type C) - 3.1 A max | 750W max, 150W LED, M3 (0.5A@0.5pf) |
| Timer range | 5min -4 hrs (+ switch mode) | NA | 20 min ramp up/ down timer | 20 min ramp up/ down timer | NA | NA | NA | NA | 10s – 15min |
| Built-in over-temp, overload, short circuit protection | Overtemp | YES | YES | YES | NA | YES | YES | YES | Overtemp |
| Compatible loads | 15A Resistive/ Incandescent<br>10A Fluro, ELV, LED<br>5A Motor (M40) | Dimmable LED, 240V Halogen, Incandescent, ELV tx | Dimmable LED, 240V Halogen, Incandescent, ELV tx | Dimmable LED, 240V Halogen, Incandescent, ELV tx | 0/1-10V active LED drivers and ceiling fans | NA | NA | NA | LED, 240V Halogen, Incandescent, ELV, iron core tx, motors |
| Depth from grid Compatible wall box | 53mm Deep | 36mm standard | 40mm standard | 40mm standard | 36mm Standard | 50mm standard | 57mm deep | 55mm deep | 41mm standard |
| No. of units in a plate | 3 (de-rating applies) | 3 (de-rating applies) | 6 (de-rating applies) | 6 (de-rating applies) | 6 | 2 | 2 | 2 | 3 |
| Application | Lighting, Fan Motors, heated towel rails, heat lamps, sockets | Lighting – LED, halogen, incandescent | Lighting – LED, halogen, incandescent | Lighting – LED, halogen, incandescent | 0/1-10V controllable drivers (e.g. LED strips, some fans) | Kitchen, bedroom, study | Kitchen, bedroom, study | Kitchen, bedroom, study | Hallway, stairs, pantry, WIR, entry, bathrooms |

clipsal.com/iconic-electrician

Iconic and Clipsal Iconic are trademarks of Schneider Electric (Australia) PTY Limited. 998-22239202_07

# Clipsal Wiser Control devices – Selection chart










| | Remote mechanisms | | Iconic connected switches | | Iconic connected dimmers | Micro Modules (for use with any wall plate) | | |
|---|---|---|---|---|---|---|---|---|
| **Product Name** | **Smart PB Remote mech with LED** | **ControlLink Remote Mech** | **Connected Switch 10AX (Zigbee)** | **Connected Switch 2AX (Zigbee)** | **Connected Dimmer (Zigbee)** | **Micro module Switch (Zigbee)** | **Micromodule Dimmer (Zigbee)** | **Micromodule Blind controller (Zigbee)** |
| Model # | 41EPBCLM-VW | 41EPBM-VW | 41E10PBSWMZ-VW | 41E2PBSWMZ-VW | 41EPBDWCLMZ-VW | CLP5011WSZ | CLP5010WDZ | CLP5015WBZ |
| Connectivity | ControlLink | NA (Momentary switch only) | BLE & Zigbee 3.0 (Zigbee default) | BLE & Zigbee 3.0 (Zigbee default) | BLE & Zigbee 3.0 (Zigbee default) | Zigbee 3.0 | Zigbee 3.0 | Zigbee 3.0 |
| 2-wire/3-wire | 3-wire (Active, Neutral, ControlLink) | 2-wire | 3-wire | 3-wire | 3-wire | 3-wire | 2-wire | 3-wire |
| Multiway control (ControlLink) | Slave/remote control | Slave/remote control | YES (Multiway switching) | Not available (use Automations) | YES (Multiway dimming) | YES (using parallel bell press switches) | YES (using parallel bell press switches) | YES (using parallel bell press switches) |
| Configurable LED indicator | YES | NO | YES | YES | YES | NO | NO | NO |
| Configurable min/max brightness | NA | NA | NA | NA | YES | NA | YES | NA |
| Max load ratings | ControlLink communication only, no direct load control | 240V 50mA | 10AX/15A Res<br>10A @0.8pf<br>M40 (6A @0.5pf) | 2AX<br>2A @0.6pf<br>2A Motor | 300W Dimmable LED<br>300W Incandescent<br>300W Halogen & ELV. | 200W LED<br>10AX , 2200W incand<br>1000VA Motor | 100W Dimmable LED<br>200W Incandescent<br>150W Halogen & ELV. | 240V twin active motor<br>4A 0.6-1.0pf |
| Timer | NA | NA | Delay timer<br>1-5hrs (as an Automation) | Delay timer<br>1-5hrs (as an Automation) | Delay timer<br>1-5 hrs (as an Automation) | Delay timer<br>1-5 hrs (as an Automation) | Delay timer<br>1-5 hrs (as an Automation) | Delay timer<br>1-5 hrs (as an Automation) |
| 24/7 Scheduler | NA | NA | YES (as an Automation) | YES (as an Automation) | YES (as an Automation) | YES (as an Automation) | YES (as an Automation) | YES (as an Automation) |
| Suitable for fan motors | NA | NO | YES | YES | NO | YES | NO | NO |
| Depth from grid compatible wall box | 39mm standard | 39mm standard | 53mm Deep | 39mm Standard | 53mm Deep | Switch plate dependent | Switch plate dependent | Switch plate dependent |
| No. of units in a plate | 6 | 6 | 3 | 6 | 3 | 6 (wired to bell press switches) | 6 (wired to bell press switches) | 6 (wired to bell press switches) |
| Applications | Provides multiway control with matching LED indicator for Wiser modules | Provides multiway control for Wiser modules | Indoor and outdoor lighting, heat lamps, outdoor IR heaters, heated towelrail, pool pumps | Indoor and outdoor lighting, small motors, exhaust fans, heated towel rails.<br>Moment triggering (via automations) | Dimmable LEDs, Incandescent and halogen lighting | Garage door and gate motors, Indoor and outdoor lighting, heat lamps, exhaust fans, heated towel rails, pool pumps | Dimmable LEDs, Incandescent and halogen lighting (31LCDA recommended for LEDs) | 240V twin active blind motors equipped with an end position switch. |

clipsal.com/wiser

Iconic and Clipsal Iconic are trademarks of Schneider Electric (Australia) PTY Limited. 998-22239202_07